





**THE DATASHEET OF  
KP13B-SF-PEJ(800)**




Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△1	2	RE-5-1567	N.J.W	S.H.C	17.02.06	△3	2	RE-5-2221	K.C.J	A.B.H	19.06.24
△2	9	RE-5-1840	K.C.J	A.B.H	17.12.12	△4	2	RE-5-2935	K.C.J	A.B.H	23.01.11
<b>APPLICABLE STANDARD</b>											
RATING	OPERATING TEMPERATURE RANGE	-40℃ ~ 85℃ (NOTE1) △4			STORAGE TEMPERATURE RANGE	-10℃ TO 60℃ (WITH PACKING) △4					
	VOLTAGE	AC 10V			OPERATING OR STORAGE HUMIDITY RANGE	95% MAXIMUM (NON-CONDENSING)					
	CURRENT	0.5A									
<b>SPECIFICATIONS</b>											
ITEM		TEST METHOD			REQUIREMENTS			QT	AT		
<b>CONSTRUCTION</b>											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT			ACCORDING TO DRAWING			X	X		
MARKING								X	X		
<b>ELECTRICAL CHARACTERISTICS</b>											
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD IEC60512-2-1		OPEN VOLTAGE 20 mV AC MAX TEST CURRENT 1mA			INITIALLY 100mΩ MAXIMUM (NOTE2)			X	-		
INSULATION RESISTANCE IEC60512-3-1 △2		MEASURE WITHIN 1 MINUTE AFTER APPLYING 500V DC			INITIALLY 1000MΩ MINIMUM			X	-		
VOLTAGE PROOF IEC60512-4-1 △2		500Vrms AC IS APPLIED FOR 1 MINUTE			① NO FLASHOVER OR BREAKDOWN ② CURRENT LEAKAGE 1mA MAXIMUM			X	X		
<b>MECHANICAL CHARACTERISTICS</b>											
MECHANICAL OPERATION [OFFICE ENVIRONMENT] EIA364B class 1.1		5,000 TIMES INSERTION AND WITHDRAWAL SHALL BE MADE AT THE CYCLE RATE LESS THAN 10 CYCLES PER 1MINUTE  NOTE : AFTER EACH 10 CYCLES STOP THE INSERTION AND REST THE CONNECTOR FOR 5 TO 10 MINUTES.  CARD SURFACE SHALL BE CLEANED BY AIR BLOW: AT EACH 100 CYCLES INTERVAL(10 TIMES) FROM START TO 1,000 CYCLES.  AT EACH 1,000 CYCLES INTERVAL(4 TIMES) FROM 1,001 CYCLES TO 5,000CYCLES.  △1			① CONTACT RESISTANCE: AFTER TEST 50mΩ MAXIMUM CHANGE  ② NO MECHANICAL DAMAGE SHALL OCCUR ON THE PARTS.			X	-		
CARD INSERTION FORCE		MEASURED BY APPLICABLE CARD AT 25±3mm/min			3 TO 7N (NOTE3)			X	-		
CARD EJECTION FORCE											
VIBRATION AND HIGH FREQUENCY IEC60512-6-4 △2		FREQUENCY 10 TO 55 TO 10 Hz/min, SINGLE AMPLITUDE 0.75mm FOR 2h IN X,Y,Z 3 DIRECTIONS, TOTAL 6h			① NO ELECTRICAL DISCONTINUITY OF 1us ② NO MECHANICAL DAMAGE SHALL OCCUR ON THE PARTS.			X	-		
SHOCK IEC60512-6-3 △2		ACCELERATION 490m/s <sup>2</sup> STANDARD HOLDING TIME 11ms, SEMI-SINE WAVE FOR 3 TIMES IN 3 DIRECTIONS, TOTAL 18 TIMES.			③ CONTACT RESISTANCE AFTER TEST 50mΩ MAXIMUM CHANGE △3			X	-		
<b>REFERENCE DRAWING</b>											
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED			
(NOTE1) : INCLUDE THE TEMPERATURE RISE BY CURRENT (NOTE2) : CONTACT RESISTANCE INCLUDES CONDUCTOR RESISTANCE UNLESS OTHERWISE SPECIFIED. THE TEST SHOULD BE DONE UNDER TEMP 15 TO 35℃. AIR PRESSURE 86 TO 106kPA, RELATIVE HUMIDITY 25 TO 85%. (NOTE3) : IT MAY BE CHANGED ACCORDING TO THE TRAY/CARD MATERIAL AND DIMENSIONS. △1				C.K.KIM 14.06.30	C.K.KIM 14.06.30	C.K.KIM 14.06.30	H.C.SONG 14.06.30				
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST											
HIROSE KOREA CO.,LTD.				SPECIFICATION SHEET			PART NO. KP13B-SF-PEJ(800)				
CODE NO.(OLD) CL		DRAWING NO. ELC4-631768			CODE NO. CL 6530-0002-9-800			1 2			

Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>ENVIRONMENTAL CHARACTERISTICS</b>				
DAMP HEAT CYCLE IEC60512-11-12	10 CYCLES(1CYCLE=24HOURS)WITH CONNECTORS ENGAGED. 			
RAPID CHANGE OF TEMPERATURE IEC60512-11-4	5 CYCLES(1CYCLE=1HOUR) WITH CARD MATED CONDITION (TEMPERATURE : -55°C TO 85°C, RELOCATION TIME TO CHAMBER : WHITIN 5MIN)	① CONTACT RESISTANCE : AFTER TEST 50mΩ MAXIMUM CHANGE  ② INSULATION RESISTANCE : AFTER TEST 100MΩ MINIMUM  ③ NO MECHANICAL DAMAGE OR HEAVY CORROSION SHALL OCCUR ON THE PARTS.	X	-
DRY HEAT IEC60512-11-9	EXPOSED AT 85°C FOR 96 HOURS WITH CARD MATED CONDITION		X	-
COLD IEC60512-11-10	EXPOSED AT -40°C FOR 96 HOURS WITH CARD MATED CONDITION		X	-
DAMP HEAT STEADY STATE IEC60512-11-3	EXPOSED AT 40°C, 90 TO 95%RH, 96 HOURS WITH CARD MATED CONDITION		X	-
HYDROGEN SULPHIDE JEIDA 38	EXPOSED IN 3 PPM HYDROGEN SULPHIDE, APPROX. 40°C, 80%RH, 96HOURS WITH CARD MATED CONDITION		X	-
CORROSION SALT MIST IEC60068-2-11	EXPOSED AT 35±2°C, 5% SALT WATER SPRAY FOR 48Hr		X	-
RECOMMENDED TEMPERATURE PROFILE	SEE THE FOLLOWING CONDITION, NUMBER OF CYCLE 1 TIME (NOTE4)		NO MECHANICAL DAMAGE OR HEAVY CORROSION SHALL OCCUR ON THE PARTS.	X



**REFERENCE DRAWING**

NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST

HIROSE KOREA CO.,LTD.	SPECIFICATION SHEET	PART NO. KP13B-SF-PEJ(800)
-----------------------	---------------------	-------------------------------

CODE NO.(OLD)	DRAWING NO.	CODE NO.	2/
---------------	-------------	----------	----

CL	ELC4-631768	CL 6530-0002-9-800	✓ 2
----	-------------	--------------------	-----

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View KP13B-SF-PEJ\(800\) on WIN SOURCE](#)
- [Hirose Electric Co Ltd Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management